

PCB terminal block — TL series (Raising Clamp)— TL217V




图 示 (Pic. shown) : TL217V-03P-G12S


General:

PCB terminal block	Rated : 320V, 24A , 4.0mm ²
Single row , 5.00mm pitch , 02-24 Pole	
Wiring orientation: 180° (wire-to-board)	
Screw clamp unit: M2.5, 0.5Nm Max	

认证 (Approval) :

技术参数 Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	320V	--
额定电流(Rated current)	20A	--	10A	--	24A	--
额定连接容量(Rated connection capacity)	24-12AWG Sol&Str			0.34-4.0mm ²		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				--		
绝缘电阻(Insulation Resistance)				500MΩ or more at DC500V		
耐电压(1分钟)(Withstanding Voltage/1Min)				2200V		
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M2.5 , 0.5Nm Max		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				7.2mm		
使用温度(Operating temperature)				-40°C up to +105°C		
焊接方式(Soldering recommend)	Wave soldering ,260°C 5S Max (Single Wave) , 260°C 10S Max(Double Wave)					

订购方式(How to order)



Web: www.china-tianli.com TEL: +86-574-6347-9600, 6389-6436 Mail: sale@china-tianli.cn
地址: 中国浙江省宁波杭州湾新区庵东工业园区纬三路138号
ADD: 138, Weisan Rd., Andong Development Zone, Hangzhou Bay Area, Ningbo, Zhejiang, China