



图示(Pic. shown) : TLB-700-1P

General: Terminal Strip Rated : 450V,32A , 4mm²
01 Pole
Wire-to-Wire Connection
Screw clamp unit: M3, 0.5Nm Max

认证 (Approval) :

| 技术参数 Technical Data | UL standard | | | IEC standard | | |
|--|----------------------|----|------|--|---------|--------|
| UL应用组别(UL Application group) | UL Application group | | | IEC过电压别/污染等级(IEC overvoltage category /pollution degree) | | |
| IEC过电压别/污染等级(IEC overvoltage category /pollution degree) | B | C | D | III / 3 | III / 2 | II / 2 |
| 额定电压(Rated voltage) | 300V | -- | 300V | -- | 450V | -- |
| 额定电流(Rated current) | 20A | -- | 10A | -- | 32A | -- |
| 额定连接容量(Rated connection capacity) | 22-12AWG Sol&Str | | | 1.5~4mm ² Sol&Str,6mm ² Sol Max | | |
| 绝缘材料(Insulation Material) | | | | Ceramic | | |
| 电流承载部件材料和镀层(Material & Plating of Current carrier) | | | | Copper alloy , Ni plated | | |
| 接线弹片材料(Material of Clamp spring) | | | | -- | | |
| 绝缘电阻(Insulation Resistance) | | | | 500MΩ or more at DC500V | | |
| 耐电压(1分钟)(Withstanding Voltage/1Min) | | | | 2000V | | |
| 额定冲击电压(Rated surge voltage) | | | | -- | | |
| 接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.) | | | | M3 , 0.5Nm Max | | |
| 固定螺丝(Mounting Screw), 扭矩(torque) | | | | -- | | |
| 剥线长度(Wire stripping length) | | | | 7.0mm | | |
| 使用温度(Operating temperature) | | | | -40°C up to +200°C | | |
| 焊接方式(Soldering recommend) | | | | -- | | |

订购方式(How to order)

