

■ 图示(Pic. shown) : TL221T-04P-KC


General.	PCB Connector	Rated : 320V,10A , 2.5mm ²
	Single row , 5.00mm pitch , 02-24 Pole	
	Wiring orientation: 90°(wire to plug-in)	
	Screw clamp unit: M2.5 , 0.4Nm Max	

认证 (Approval) :



■ 技术参数 Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	320V	320V	630V
额定电流(Rated current)	10A	--	10A	12A	12A	12A
额定连接容量(Rated connection capacity)	24-14AWG Str			0.34-2.5mm ²		
绝缘材料(Insulation Material)	PA66 UL94 V-0					
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Tin plated					
接线弹片材料(Material of Clamp spring)	--					
绝缘电阻(Insulation Resistance)	500MΩ or more at DC500V					
耐电压(1分钟)(Withstanding Voltage/1Min)	1600V					
额定冲击电压(Rated surge voltage)	4000V					
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)	M2.5 , 0.4Nm Max					
固定螺丝(Mounting Screw) , 扭矩(torque)	--					
剥线长度(Wire stripping length)	6.0mm					
使用温度(Operating temperature)	-40°C up to +105°C					
焊接方式(Soldering recommend)	--					

■ 订购方式(How to order)



■ 针座 (Pin header) — single row



P/N : TL205P

Wiring orientation :

90° (plug-in to board)

Rated : 320V,12A