


Terminal Strip — TLB series — TLB-200W



■ 图示(Pic. shown) : TLB-200W-12P-T01S

General:	Terminal Strip	Rated : 450V,32A , 4mm ²
	10.00mm pitch , 02-12 Pole	
	Wire-to-Wire Connection	
	Screw clamp unit: M3, 0.5Nm Max	

认证 (Approval) :

■ 技术参数 Technical Data	UL standard			IEC standard		
	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	300V	300V	--	450V	--
额定电流(Rated current)	30A	30A	10A	--	32A	--
额定连接容量(Rated connection capacity)	22-10AWG Sol&Str			0.75-4mm ²		
绝缘材料(Insulation Material)				PA66 UL94 V-2		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Ni plated		
接线弹片材料(Material of Clamp spring)				--		
绝缘电阻(Insulation Resistance)				500M Ω or more at DC500V		
耐电压(1分钟)(Withstanding Voltage/1Min)				2500V		
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M3 , 0.5Nm Max		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				5-6.0mm		
使用温度(Operating temperature)				-40°C up to +80°C		
焊接方式(Soldering recommend)				--		

■ 订购方式(How to order)

