



- NOTES:**
- UL:
Rating:300V, 20A
Insulation Withstands Voltage:AC1600V/MIN
Suitable Electric Wire:26AWG~12AWG
 - IEC:
Rating:320V, 24A
Rate Impulse Voltage:4000V
Insulation Resistance:500MΩ or more at DC500V
Contact Resistance: ≤5mΩ
Material Group: I
Pollution Degree:2
Overvoltage Category:III
Suitable Electric Wire:0.2mm²~2.5mm²/4mm² (Sol)
 - Using Temperature Range:-40℃~+115℃
 - Strip length:10mm
 - RoHS compliance

DIM	P	1	2	3	4	5	6	7	8	9	10	11	12					
		L	6.4	11.4	16.4	21.4	26.4	31.4	36.4	41.4	46.4	51.4	56.4	61.4				
		A	0	5	10	15	20	25	30	35	40	45	50	55				
DIM	P	13	14	15	16	17	18	19	20	21	22	23	24					
		L	66.4	71.4	76.4	81.4	86.4	91.4	96.4	101.4	106.4	111.4	116.4	121.4				
		A	60	65	70	75	80	85	90	95	100	105	110	115				
A	Total Pitch Tolerances in mm						Nominal dimension range in mm											
	over	over	over	over	over	over	over	over	over	over	over	over	over					
	0	30	53	70	90	115	150	200	250	0	30	53	70	90	115	150	200	250
	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±1.00	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	±1.20	

4	SPRING COIL	P	STAINLESS STEEL	/
3	SOLDER.PIN	P	Copper Alloy	Tin Plated
2	COVER	1	PA66	UL94V-0
1	HOUSING	P	PA66	UL94V-0
ITEM	NAME OF PART	Q'TY	MATERIAL	NOTE

DWG.	CZM	DATE	2020.11.09	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	2.5: 1	A4	
APP.		DATE		TLM-212R-XXP-X			
 ELECTRICAL MACHINERY(NINGBO)CO.,LTD.							
				DWGN0	TLDW-TLM212RXXPX		